



# HR-Sense

# Cyber Series BIOMETRIC

The Cyber Series Biometric is a time and data collection terminal that sets a new standard in the industry with the proven E-field sensor technology. This method of fingerprint recognition distinguishes a ridge from a valley with sensors located on a one inch by one inch pod. The Cyber Series is able to provide security that will save your company money through the elimination of buddy punching and time theft. Enjoy all the benefits of Biometric technology in the Cyber Series without having to break the bank.



- Single or multi-clock environment
- Up to 1 MB of RAM
- EIA Standard RS 232 or RS 485 compatible
- 10/100 BaseT Ethernet
- Fingerprint E-field sensor technology
- On-board setup and diagnostics utility
- Digital bar code wand port
- Expansion slot for support of plug-in options
- Optional ability to cold search templates
- Durable and industrial housing

[www.ssipr.com](http://www.ssipr.com)

# HR-Sense

# Cyber Series

## BIOMETRIC

## Specifications

<b>DISPLAY</b>	4 line x 20 character backlit, super-twist LCD
<b>CLOCK</b>	12 or 24 hour format – USA or International (quartz precision) Time stamp of data transactions
<b>KEYPAD</b>	Software defined function keys Large 20 key tactile 4x5 matrix Custom user-defined keypad legends
<b>MEMORY</b>	Up to 1 MB of RAM available UP to 512KB Flash memory
<b>PROGRAMMING</b>	ATS Universal Command Set™ modules, C programming language or third party custom application packages
<b>SELF-TEST</b>	ACCU-RATE™ on-board set-up and full-feature diagnostics
<b>INTERFACE</b>	TCP/IP Ethernet 10/100-base-T 802.3 (optional) EIA Standard RS232 or RS485 Standard AT Command Set for 33.6K Baud modem (optional) DI/DO or serial interface printer port (optional)
<b>ENCLOSURE</b>	Die cast aluminum housing with key-lockable base
<b>POWER</b>	+10 to +17 VDC (+12 VDC Nominal) Non-interruptible power source with charger (optional)
<b>ENVIRONMENT</b>	Operation: 32" to 110 F (0 to 43 C)
<b>PHYSICAL</b>	7.25" x 9.75" x 3.8" Weight: 6 lbs. (18.42cm x 24.77cm x 9.65cm Weight: 2.72 kg)
<b>ACCESSORIES</b>	Integrated/External visible/infrared bar code slot readers Integrated magnetic slot readers Integrated/External proximity readers Solid state or dry contact relay modules Serial interface printer port



### Sense Software International

PO Box 193095  
San Juan, PR 00919-3095

Tel: 787.282.8047  
Fax: 787.250.1159  
Email: sales@ssipr.com

[www.ssipr.com](http://www.ssipr.com)

Sense Software Intl. and Accu-Time, whose policy is one of continuous improvement, reserves the right to change specifications without notice.

**Cyber Series Configuration Guide**