



HR-Sense

Cyber Series

The Sense Software/Accu-Time Cyber Series is designed for workforce management applications such as employee time and attendance for payroll, access control, and job tracking. This cost-effective Cyber terminal is a programmable data collection device with features previously reserved for the most expensive platforms. The selectable serial or Ethernet (10/100 Base T) communications and optional PCMCIA-type Cyber Port offers countless configuration options that make the Cyber Series second to none.



- 1 MB RAM options
- 512KB Flash option
- Serial RS232 or RS485
- 10/ 100 Base-T Ethernet
- Digital bar code wand port
- 33.6K Baud modem option
- 802.11 b Radio Frequency option
- Option cards compatible with ATS Cyber Port
- DI/DO port for access control or bell ringing
- Dual proximity readers

www.ssipr.com

HR-Sense

Cyber Series

Specifications

DISPLAY	2 or 4 line x 20 character backlit, super-twist LCD
CLOCK	12 or 24 hour format – USA or International (quartz precision) Time stamp of data transactions
KEYPAD	Software defined function keys Large 20 key tactile 4x5 matrix Custom user-defined keypad legends
MEMORY	Up to 1 M of RAM available UP to 512KB Flash memory
PROGRAMMING	ATS Universal Command Set™ modules, C programming language or third party custom application packages
SELF-TEST	ACCU-RATE™ on-board terminal set-up and full-feature diagnostics
INTERFACE	TCP/IP Ethernet 10/100-base-T 802.3 (optional) EIA Standard RS232 or RS485 Standard AT Command Set for 33.6K Baud modem (optional) DI/DO or serial interface printer port (optional)
ENCLOSURE	Die cast aluminum housing with optional key-lockable base Gull-back mounting (optional)
POWER	+10 to +17 VDC (+12 VDC Nominal) Non-interruptible power source with charger (optional)
ENVIRONMENT	Operation: 32" to 110 F (0 to 43 C)
PHYSICAL	7.0" x 7.25" x 3.4" Weight: 4 lbs. (17.78cm x 18.42cm x 8.64 m Weight: 1.8 kg)
ACCESSORIES	Integrated/External visible/infrared bar code slot readers Integrated magnetic slot readers Integrated/External proximity readers Solid state or dry contact relay modules Serial interface printer port



Sense Software International

PO Box 193095
San Juan, PR 00919-3095

Tel: 787.282.8047
Fax: 787.250.1159
Email: sales@ssipr.com

www.ssipr.com

Sense Software Intl. and Accu-Time, whose policy is one of continuous improvement, reserves the right to change specifications without notice.

Cyber Series Configuration Guide

Term. Type	Display	Serial	Ethernet		Modem	Memory	Flash	Slots	Mounting	Pros.	DI/DO
			10M	10/100M							
CSS	2x20	Std	-	-	Opt	128K	256K	-	Gull	-	-
CSE	2x20	-	Std	-	-	128K	256K	-	Gull	-	-
CS1	4x20	Std	-	-	Opt	512K	256K	-	Lock	Opt	Opt
CS2	4x20	Std	-	Std	Opt	512K	256K	-	Lock	Opt	Opt
CS3	4x20	Std	-	Std	Opt	1M	512K	1	Lock	Opt	Opt